

Caesium iodide spherical surface lenses

The most frequently requested specifications for caesium iodide lenses are as follows:

Focal length	up-to 5000 ± 0.1mm or 1% whichever largest
Back focal length	up-to 5000 ± 0.1mm or 1% of focal length
Radius of curvature, S1	up-to 5000 ± 5 fringe across surface
Radius of curvature, S2	up-to 5000 ± 5 fringe across surface
Form error, S1	1 fringe from test sphere
Form error, S2	1fringe from test sphere
Centration (arc second)	less than 60
Centre thickness	up-to 10 ± 0.1mm
Edge thickness	minimum 1mm or 1% of centre thickness
Length of aperture	up-to 100 ± 0.1mm
Width of aperture	up-to 100 ± 0.1mm
Diameter	100 ± 0.1mm
Clear aperture	90% of diameter
Edge finish	blacked, ground
Chamfer	0.3x0.3@45°
Surface quality	40-20 scratch/ dig

Coatings

BBAR coating @ 2-14µm

Diamond-Like Carbon coating (DLC) @2-14µm

Our capabilities are always expanding so if your requirement is not mentioned above please enquire as we have many years of experience in this field.

Contact our multilingual technical sales team and discover how Knight Optical's high quality caesium iodide spherical lens capabilities and service can improve your instrumentation and supply chain experience.