
ALL PARTS TO BE FREE FROM BURRS, SHARP EDGES, CORROSION AND SCRATCHES ISSUE

INTRODUCED

ECN N°

BREAK EDGES .15X45 CHAMFE	CR /		
1.5	<del>-</del>	· \	
<b>1</b>	1	Ī	
			\
		ω,	>
	N 2	26.5	\$ 05
<u> </u>		•	
		· <u> </u>	
/2	-		
M26.5X.5 PITCH			





Copyright
This document and the copyright therein are the property of Knight Optical (UK) Ltd, and may not be used, copied or disclosed to any third party without written authorisation from Knight Optical (UK) Ltd.

UNLESS OTHERWISE STATED DRAWING STANDARDS TO B.S.308 1,2,3. MACHINED FACES  $\frac{32}{\sqrt{}}$  MICRONS TOLERANCES:- LINEAR +/- 0.1mm ANGULAR +/- 0.5°

MATERIAL	DRAWN BY	TITLE MOSE SY E DITCH OF	^ N A D . C	NINO	
6082 ALI	M ALDRIDGE	M25.5X.5 PITCH CLAMP RING			
TREATMENT	DATE	SUB TITLE SUB T	TLE		
BLK ANDDISE	27/01/14				
FINISH	SCALE	DRG N°	SHT	OF	
	1:1	"HLF2500 (PART 2)	2	2	